A Generic Coupler for Data Registration, Match, and Model Coupling

Shujia Zhou NASA GSFC SIVO/Northrop Grumman

Contributors:

Joseph Spahr (UCLA)
Carlos Cruz (NASA GSFC SIVO/Northrop Grumman)


*This work was funded by the NASA ESTO/CT Project

Outline

- Background in Earth system model coupling via components
 - A tool is needed to reduce complexity in coupling among hierarchical components
- Generic Coupler
 - Architecture
 - Current capabilities
- Summary
- Next step


Earth System Model Coupling

- Several ways of coupling
 - > Many to one
 - > One to one
 - **➤** One to many




ESMF Component and State


- An ESMF model component should be developed independent of other components
 - ➤ Its functions are "producer" only while its data are "producer" (export) as well as "consumer" (import)
- Couplers resolve all the mismatches to ensure model components to interact



ESMF Component, State, Coupling




Generic Coupler: Standard Name (e.g., CF) in Coupling




Presented in the ESMF Community Meeting, MIT, August 2005

Generic Coupler



Presented in the conference of Parallel Computational Fluid Dynamics 2005



ESMF Component Coupling


Coupling tasks

An export variable of a component (1) matches, (2) transports, and (3) transforms (if needed) to an import variable of the other component

ESMF utilities

- ESMF State is used to contain those variables and perform match
 - ESMF_StateAddNameOnly(exportState, "U", rc)
 - ESMF_StateIsNeeded(importstate, dataname(I), rc)
- Nested ESMF State is used to deal with coupling with multiple components
- Nested ESMF component is used to deal with hierarchy component
- ESMF coupler is used to deal with the variable transformation such as regridding and unit conversion.

New Generic Coupler



ESMF Component Coupling: Match

- "Match" task
 - Generic Coupler does it outside the user code directly with the string matching

ESMF Component Coupling: Transport

- "Transport" task
 - If there is no need for transformation, then assigning the export variable to its matched import variables via pointers or copies.
 - If there is a need for transformation, then ESMF state and coupler are needed.
 - A ESMF component needs to use nested ESMF state to contain all the matched export variables of its children component
 - Generic Coupler uses a tree data structure

ESMF Component Coupling: Coupling

- If an export variable of a component (e.g., "DYN") has been matched to an import variable of the other component "OCN" and transported to the grand parent (e.g., "ATM") which is the sibling to the component "OCN".
 - A coupler is needed to transform the variable as needed via regrid and unit changes etc.
 - To ensure flexibility, *Generic Coupler* provides the stub code for users to customize.

Input For Generic Coupler

One input plain text file

- > component name
- import field name
- export field name
- child component name
- parent component name
- local name

Advantage

- > Easy-to-use
- > Less intrusion
- Dynamic configuration

componentstart AGCM

childstart

SDYN PHYS

childend

parentstart

GCM

AANA

parentend

importstatestart

DUDT

DVDT

DTDT

DPEDT

DQVDT DO3DT

importstateend

exportstatestart

DUDT_ANA

DVDT ANA

DTDT_ANA

DPEDT_ANA

DQVDT_ANA

DO3DT_ANA

QVFILL

O3FILL

TROPP

TROPT TROPQ

exportstateend

componentend

Example with AGCM of GEOS5

Output of Generic Coupler

- All the connections from the matched export to import field names
 - ➤ Create the stub code of ESMF components with matched import/export field variables
 - > Diagram the connection relationship automatically
- The connections can be filtered with the information of component hierarchy tree
 - > Only the couplers between the siblings will be created
- The component has the import/export field names of its child components

Use of Generic Coupler


To run

• gc.exe inputFile outLogFile outConnectFile selectComponent


To create a connection diagram

• dot outConnectFile.dot -Tjpg > outConnectFile.jpg


Component Hierarchy Tree in GEOS-5




Partial Component Export-To-Import Pair Relationship in GEOS-5



Component Export-To-Import Pair Relationship in PHYS of GEOS-5



Component Export-To-Import Pair Relationship in SURF of GEOS-5



ESMF Component Stub Code (Sample): AGCM

Only those matched field variables are created.

ESMF Component Stub Code (Sample): AGCM (Continued)

```
subroutine AGCM register(comp, rc)
type(ESMF GridComp), intent(inout):: comp
integer, intent(out) :: rc
ESMF_GridCompSetEntryPoint(comp, ESMF_SETINIT, AGCM_init1, 1, rc)
ESMF GridCompSetEntryPoint(comp, ESMF SETRUN, AGCM run, ESMF SINGLEPHASE, rc)
ESMF GridCompSetEntryPoint(comp, ESMF SETFINAL, AGCM final, ESMF SINGLEPHASE, rc)
end subroutine
subroutine AGCM init1(gcomp, importState, exportState, clock, rc)
type(ESMF GridComp), intent(inout):: gcomp
type(ESMF State), intent(inout):: importState, exportState
type(ESMF Clock), intent(in):: clock
integer, intent(out) :: rc
ESMF StateAddField(importState, field DPEDT, rc)
ESMF StateAddField(importState, field DTDT, rc)
ESMF StateAddField(importState, field DUDT, rc)
ESMF_StateAddField(importState, field_DVDT, rc)
ESMF_StateAddField(exportState, field_TROPP, rc)
end subroutine AGCM init1
```

No more matching for field variables

Summary

- A data registration and match tool has been developed to facilitate ESMF component coupling, in particular coupling among hierarchical components
 - Generate ESMF stub codes of components and couplers
 - Generate diagrams showing the export-to-import pair relationship among components.

Next Step

- User interface will be refined with the feedback
 - Input text file
 - API
- Assemble components and execute
 - CCA-style?

